

AC-33 TYRE SHINE

SECTION 1 – STATEMENT OF CHEMICAL PRODUCT AND COMPANY IDENTIFICATION			
Trade Name:	AC-33 TYRE SHINE		
SUPPLIER:	AUSTECH CHEMICALS PTY LTD		
ADDRESS:	45 MAGNESIUM ST, NARANGBA QLD 4504 Australia		
TELEPHONE:	07 3204 8511	FAX:	07 3807 7491
EMERGENCY PHONE:	Phone Australia 131126 or New Zealand 0800 764 766	ABN:	84 124 370 761
Substance:	Solvent based liquid	Product Use:	Tyre gloss
Creation Date:	August 2021	Revision Date:	August 2026

SECTION 2 – HAZARDS IDENTIFICA	ATION	
Classification of the substance or	mixture	
Poisons Schedule	S5 (liquid hydrocarbons)	
Dangerous Goods	Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. • FLAMMABLE LIQUID CLASS 3.2	
GHS Classification	Classified as Hazardous according to the Globally Harmonised System of Classification and	
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.	
	Flammable Liquids Category 2	
	Eye Irritation Category 2A	
	Skin Irritation Category 2	
	Specific Target Organ Toxicity – Single Exposure Category 3	
	Aspiration Hazard - Category 1	
	Acute Aquatic Toxicity - 2 /Chronic Aquatic Toxicity - 2	
Label elements		
	GHS08 GHS02 GHS07 GHS09	
Signal word	DANGER	
Hazard statement(s)		
H225	Highly flammable liquid and vapour.	
H319	Causes serious eye irritation.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H304	May be fatal if swallowed and enters airways.	
H401/411	Toxic to aquatic life with long-lasting effects.	
Precautionary statement(s): Prev	ention	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.	
P233	Keep container tightly closed.	
P240	Ground and bond container and receiving equipment. P241 – Use explosion-proof [electrical/ventilating/lighting/] equipment.	



AC-33 TYRE SHINE

Issue Date: 23.08.2021 Version #5.0

P242	Use non-sparking tools.	
P243	Take action to prevent static discharges.	
P264	Wash hands and skin thoroughly after handling	
P261	Avoid breathing dust/fume/ gas/mist/ vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
Precautionary statement(s): Resp	onse	
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P331	Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P321	Specific treatment (see First Aid Measures on this label).	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P305 + P351 + P338	" IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if	
	present and easy to do. Continue rinsing.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	
P304+P340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P370+P378	In case of fire: Use foam, water spray or fog, dry chemical powder to extinguish. Do not use water in a jet.	
P391	Collect spillage.	
Precautionary statement(s): Store	age	
P405	Store locked up.	
P403 + P235+P233	Store in a well-ventilated place. Keep cool. Keep container tightly closed.	
Precautionary statement(s): Disposal		
P501	Dispose of contents/ container in accordance with local regulations.	
Note		
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its concentrated form, as supplied. Good hygiene and housekeeping practices should be adhered to.	

SECTION 3 – COMPOSITION AND INFORMATION ON INGREDIENTS		
Ingredients:	CAS Number:	Proportion:
Solvent Naphtha	64742-89-8	>60% w/w
n-Hexane	110-54-3	10 – 30% w/w
Note – product contains < 0.1%		
benzene		

NOTE: Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication "List of Designated Hazardous Substances" or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication "Approved Criteria for Classifying Hazardous Substances", or have been found NOT to meet the criteria of a dangerous substance as defined in the GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS). Listed ingredients may be below the cut-off concentrations for classification as hazardous, but are listed for information purposes and for additive effects.

SECTION 4 – FIRST AID MEASURES		
Inhalation	Remove victim to fresh air away from exposure. Obtain medical attention if symptoms occur.	
Skin contact	Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash	
	before re-use. Seek medical advice (e.g. doctor) if irritation, burning or redness persists.	



AC-33 TYRE SHINE

Issue Date: 23.08.2021 Version #5.0

Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. If symptoms persist, seek medical attention.
Ingestion	Do NOT induce vomiting. Do NOT attempt to give anything by mouth to an unconscious person. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).
Advice to Doctor	Treat symptomatically.
Scheduled Poisons	Poisons Information Centre in each Australian State capital city or in Christchurch, New Zealand can provide additional assistance for scheduled poisons. (Phone Australia 131126 or New Zealand 0800 764 766).
First Aid Facilities	No special requirements.

SECTION 5 – FIRE FIGHTING MEASURES		
Fire and Explosion	Product is a highly flammable liquid. Vapour accumulation could flash and/or explode if in contact	
Hazards	with open flames.	
Extinguishing Media	Foam, water spray or fog, dry chemical powder. Do not use water in a jet.	
Fire Fighting	Keep containers exposed to extreme heat cool with water spray. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion or decomposition. Do not use direct water jets on the burning product; they could cause splattering and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.	
Flash Point	<0°C	

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Emergency Procedures

In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. Stop or contain leak at the source if safe to do so. Avoid direct contact with released material. Stay upwind. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. It is recommended to eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). If required, notify relevant authorities according to all applicable regulations.

Clean Up Procedures

Soak up spilled product using absorbent non-combustible material such as sand or soil. Avoid using sawdust or cellulose. When saturated, collect the material and transfer to a suitable, labelled chemical waste container and dispose of promptly. Large Spills: Water spray may reduce vapour but may not prevent ignition in closed spaces.

Containment

Prevent product from entering sewers, rivers, waterways or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. Large spillages may be cautiously covered with foam, if available, to limit fire risk. Do not use direct jets. When inside buildings or confined space, ensure adequate ventilation. Absorb spilled product with suitable non-combustible materials. Collect free product with suitable means. Transfer collected product and other contaminated materials to suitable tanks or containers for recycle, recovery or safe disposal.

Environmental Precautionary Measures

This material is not expected to present any environmental problems other than those associated with oil spills.



AC-33 TYRE SHINE

SECTION 7 – HANDLING AN	D STORAGE
Handling	Take precautionary measures against static electricity. Avoid splash filling of bulk volumes when handling hot liquid product. Avoid contact with skin. Avoid breathing fume/mist. Prevent the risk of slipping. Use personal protective equipment as required. For more information regarding protective equipment and operational conditions for a substance which is classified according to classification notes, see exposure scenarios. These risk management measures represent a worst case. For a non-classified substance proportionate information may be found in the Safety Data Sheet
Storage	Storage area layout, tank design, equipment and operating procedures must comply with the relevant national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidizing agents.

SECTION 8 – EXPOSURE	CONTROLS AND PERSONAL PROTECTION
Exposure Limits	National Occupational Exposure Limits, as published by National Occupational Health & Safety Commission: Time-weighted Average (TWA): None established for product. However, the following may be adopted. ACGIH TWA: 5mg/m3. • n-Hexane 72 mg/m3 Short Term Exposure Limit (STEL): None established for product. However, the following may be adopted. STEL: 10mg/m3 OSHA TWA: 5mg/m3.
Ventilation	Ensure ventilation is adequate to maintain air concentrations below exposure standards. Avoid generating mists of the product. Use only in a well-ventilated area. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Ensure compliance with applicable exposure limits.
Personal Protective Equipment	Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. The following protective equipment should be available;
Eye Protection	Safety glasses with full face shield should be used for handling concentrate in quantity, cleaning up spills, decanting, etc. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material such as butyl rubber, natural latex, neoprene, PVC and nitrile — to handle in quantity, clean up spills, decanting, etc. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective workwear, e.g. rubber or plastic apron, sleeves, boots and cotton overalls buttoned at neck and wrist are recommended. Chemical resistant apron is recommended where large quantities are handled.
Respirator	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Non-viscous liquid	Colour	Water white liquid
Odour	Characteristic	Specific Gravity	0.72 - 0.77 @ 20 °C



AC-33 TYRE SHINE

Boiling Point	Typical 40 - 120 °C	Freezing Point	Not available
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	Typical <0 °C (CC)	Flammable Limits	1.0 – 6.0% (typical)
Water Solubility	Not miscible	pH	Not applicable
Volatile Organic	2000/11/11	Per Cent Volatile	85 % v/v
Compounds (VOC)	>80 % v/v		
Viscosity	Not available	Odour Threshold	Not available

SECTION 10 – STABILITY AND REACTIVITY		
Reactivity	Stable at normal temperatures and pressure.	
Conditions to Avoid	Extremes of temperature and direct sunlight. Heat, sparks, flame and build-up of static electricity.	
Incompatibilities	Incompatible with Strong oxidizers such as hydrogen peroxide, nitric acid, sulphuric acid and sources of ignition.	
Hazardous	Product does not decompose at ambient temperatures. Combustion forms carbon dioxide, and if	
Decomposition	incomplete, carbon monoxide and smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.	

SECTION 11 – TOXICOLOGICAL INFORMATION	
POTENTIAL HEALTH EFFECT	'S
No adverse health effects ex	xpected if the product is handled in accordance with this Safety Data Sheet and the product label.
Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:	
Inhalation	Mists and vapours generated may cause irritation of the upper respiratory tract. Inhalation of high concentration may lead to headache, dizziness, nausea, vomiting, drowsiness or narcosis.
Skin contact	May cause irritation to the skin that may result in redness, itchiness and swelling. Repeated or prolonged contact may dry and defat the skin, resulting in skin irritation and possibly lead to dermatitis.
Eye contact	May cause irritation in contact with the eyes, which can result in redness, stinging and tearing.
Ingestion	Harmful, may cause lung damage if swallowed. Ingestion of this product will irritate the gastric tract causing nausea and vomiting. Aspiration into the lungs may result in chemical pneumonitis.
Chronic exposure	Prolonged or repeated skin contact may cause skin irritation leading to dermatitis. Repeated or prolonged inhalation of high vapour concentrations can cause drowsiness and lead to narcosis or death.
Toxicology Information	Not toxic, based on ingredients. Oral LD50 (ATE calculated): >5,000 mg/kg
Carcinogen Status	
NOHSC	No significant ingredient is classified as carcinogenic by NOHSC.
NTP	No significant ingredient is classified as carcinogenic by NTP.
IARC	No significant ingredient is classified as carcinogenic by IARC.
Respiratory sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	Not expected to be a skin sensitizer.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.
Aspiration Hazard	Category 1 aspiration hazard.

SECTION 12 – ECOLOGICAL INFORMATION	
Eco-toxicity	Acute Aquatic Toxicity Category 2
Product (as sold)	H401 / H411 - Toxic to aquatic life with long-lasting effects.
	Acute Aquatic Toxicity (ATE calculated): 1 – 11 mg/L.
	Spills may form a film on water surfaces causing physical damage to organisms.
	Oxygen transfer could also be impaired.



AC-33 TYRE SHINE

Persistence and degradability	Expected to be biodegradable. Degrades rapidly in air by photo-chemical means.
Bio accumulative potential	Has the potential to bioaccumulate.
Mobility in soil	Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.
Other adverse effects	Not available
Environmental Protection	Do not discharge this material into waterways.

SECTION 13 – DISPOSAL CONSIDERATIONS	
	Dispose of waste according to applicable local and national regulations. Do not allow into drains or
	watercourses or dispose of where ground or surface waters may be affected. Wastes including
	emptied containers are controlled wastes and should be disposed of in accordance with all
	applicable local and national regulations.

SECTION 14 – TRANSPORT	INFORMATION
Labels Required	
ADG	Classified as Dangerous Goods.
IMDG Marine Pollutant	Yes
HAZCHEM	3YE
Land Transport (ADG)	
UN Number	UN 1993
Shipping Name:	FLAMMABLE LIQUIDS N.O.S. (N-HEXANE, SOLVENT NAPHTHA)
ADG Code	None allocated.
HAZCHEM Code	3YE
Special Provisions	TP1,TP8, TP28
Packing Group	l II
Packaging Method	P001, IBC02
Segregation	Segregation Class 3 – Flammable liquid shall not be loaded in the same vehicle or packed in the same freight container with: Class 1, Explosives Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk Class 2.3, Toxic Gases Class 4.2 Spontaneously Combustible Substances Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides Class 6 Toxic Substances (where the flammable liquid is nitromethane)
	Class 7 Radioactive Substances.
	Foodstuff and foodstuff empties.

SECTION 15 – REGULATORY	INFORMATION
GHS Classification	Classified as Hazardous according to the Globally Harmonised System of Classification and
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
SUSMP	S5 (Hydrocarbon liquid)
ADG Code	DG Class 3.2



AC-33 TYRE SHINE

Issue Date: 23.08.2021 Version #5.0

AICS All ingredients present on AICS.

Jeans Date	ORMATION
Issue Date	23 rd August 2021
Version Number	V 5.0 GHS7 classification
Abbreviations and	ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.
acronyms	AICS: Australian Inventory of Chemical Substances.
	CAS Number: Chemical Abstracts Service Registry Number.
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	HAZCHEM: An emergency action code of numbers and letters which gives information to emergency services
	HSIS: Hazardous Substances Information System
	IARC: International Agency for Research on Cancer.
	NOHSC: National Occupational Health and Safety Commission.
	NTP: National Toxicology Program (USA).
	SDS: Safety Data Sheet
	STEL: Short Term Exposure Limit.
	SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.
	TWA: Time Weighted Average.
	UN Number: United Nations Number.
Literature references	Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work Australia)
	GHS Hazardous Chemical Information List (Safe Work Australia)
	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.
	Global Harmonized System of Classification and Labelling of Chemicals (GHS)
	"Australian Exposure Standards". Safework Australia
	Australian Code For The Transport Of Dangerous Goods By Road And Rail
	Standard for the Uniform Scheduling of Medicines and Poisons
	Material Safety Data Sheets – individual raw materials – Suppliers
	HSIS – Hazardous Substance Information System – National Safe Work Australia Data Base.
	HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.
	ECHA – European Chemicals Agency
Disclaimer	This MSDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.